

**Applications:**  
S.-F.T.P. Shielded Foiled Twisted Pairs cable cat. 5e UL/ETL verified for Local Area Network – LAN cables, for assembled cables or mobile installations.

For **RJ 45 8 Pin shielded** connectors  
Standards: **EIA/TIA 568.**

**Characteristics:**

Conductors: **stranded in O.F.C. red copper**  
Cond. insulation: **PE**  
Pair colours: **White/blue-Blue, White/orange-Orange, White/green-Green, White/brown-Brown**  
I° Shield: **Aluminium tape covering 100%**  
Drain wire: **stranded in tinned copper**  
II° Shield: **Braided covering 70% O.F.C. tinned copper**  
External Sheath: **PVC**  
Sheath colour: **Blue-night**



tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C701	4x2	4 x 2 x 26 (0,14 mm <sup>2</sup> )	7x0,15	0,9		7,0	100 500	B B	6,0

Notes:

Conductor Resistance $\Omega/\text{Km} \pm 5\%$	Impedance $\Omega \pm 5\%$ $1 \div 100 \text{ MHz}$	Max Rated Voltage AC - V
140	100	49
		Operative Temperature °C -15 / +70